

Banshee Pipe Instructions

1. Jet the stock carbs with the supplied 260 main jets. The needle clip should be in the stock location and we recommend installing #30 pilot jets (Yamaha part# 260-14142-30-00).
2. Remove the airbox snorkel from the top of the airbox. Be sure to keep the airbox lid/cover on.
3. Use either super unleaded fuel or VP C-12 race gas with a 32:1 mixing ratio.
4. FMF pipes work only with FMF silencers. They will not mount to stock OEM silencers.
5. Plastic may need to be trimmed in some cases for proper clearances.

000751-070213

Banshee Pipe Instructions

1. Jet the stock carbs with the supplied 260 main jets. The needle clip should be in the stock location and we recommend installing #30 pilot jets (Yamaha part# 260-14142-30-00).
2. Remove the airbox snorkel from the top of the airbox. Be sure to keep the airbox lid/cover on.
3. Use either super unleaded fuel or VP C-12 race gas with a 32:1 mixing ratio.
4. FMF pipes work only with FMF silencers. They will not mount to stock OEM silencers.
5. Plastic may need to be trimmed in some cases for proper clearances.

000751-070213

Banshee Pipe Instructions

1. Jet the stock carbs with the supplied 260 main jets. The needle clip should be in the stock location and we recommend installing #30 pilot jets (Yamaha part# 260-14142-30-00).
2. Remove the airbox snorkel from the top of the airbox. Be sure to keep the airbox lid/cover on.
3. Use either super unleaded fuel or VP C-12 race gas with a 32:1 mixing ratio.
4. FMF pipes work only with FMF silencers. They will not mount to stock OEM silencers.
5. Plastic may need to be trimmed in some cases for proper clearances.

000751-070213

Banshee Pipe Instructions

1. Jet the stock carbs with the supplied 260 main jets. The needle clip should be in the stock location and we recommend installing #30 pilot jets (Yamaha part# 260-14142-30-00).
2. Remove the airbox snorkel from the top of the airbox. Be sure to keep the airbox lid/cover on.
3. Use either super unleaded fuel or VP C-12 race gas with a 32:1 mixing ratio.
4. FMF pipes work only with FMF silencers. They will not mount to stock OEM silencers.
5. Plastic may need to be trimmed in some cases for proper clearances.

000751-070213

Banshee Pipe Instructions

1. Jet the stock carbs with the supplied 260 main jets. The needle clip should be in the stock location and we recommend installing #30 pilot jets (Yamaha part# 260-14142-30-00).
2. Remove the airbox snorkel from the top of the airbox. Be sure to keep the airbox lid/cover on.
3. Use either super unleaded fuel or VP C-12 race gas with a 32:1 mixing ratio.
4. FMF pipes work only with FMF silencers. They will not mount to stock OEM silencers.
5. Plastic may need to be trimmed in some cases for proper clearances.

000751-070213

Banshee Pipe Instructions

1. Jet the stock carbs with the supplied 260 main jets. The needle clip should be in the stock location and we recommend installing #30 pilot jets (Yamaha part# 260-14142-30-00).
2. Remove the airbox snorkel from the top of the airbox. Be sure to keep the airbox lid/cover on.
3. Use either super unleaded fuel or VP C-12 race gas with a 32:1 mixing ratio.
4. FMF pipes work only with FMF silencers. They will not mount to stock OEM silencers.
5. Plastic may need to be trimmed in some cases for proper clearances.

000751-070213